



POST OFFICE BOX 215  
AMITE, LOUISIANA 70422

OFFICE (985) 748-3211  
FAX (985) 748-7576

**ROBBY MILLER**  
PARISH PRESIDENT  
**NOTICE TO BIDDERS**

NOTICE IS HEREBY GIVEN THAT SEALED BIDS WILL BE RECEIVED BY THE TANGIPAHOA PARISH GOVERNMENT UNTIL, THURSDAY, DECEMBER 5, 2019 AT 10:00 A.M. IN THE TPC CHAMBERS, 206 E. MULBERRY STREET, AMITE, LOUISIANA ON THE FOLLOWING:

**TWO (2) OR MORE NEW CURRENT YEAR MODEL  
12-16 YARD DUMP BODY**

THEN AND THERE BIDS WILL BE OPENED AND READ ALOUD. BIDS RECEIVED AFTER THE SPECIFIED TIME AND DATE WILL NOT BE OPENED OR RECOGNIZED.

SPECIFICATIONS MAY BE PICKED UP AT THE OFFICE OF THE TANGIPAHOA PARISH GOVERNMENT BETWEEN THE HOURS OF 8:00 A.M. B 4:00 P.M., MONDAY THROUGH FRIDAY.

TANGIPAHOA PARISH GOVERNMENT OFFICIAL BID DOCUMENTS ARE AVAILABLE AT CENTRAL BIDDING. ELECTRONIC BIDS ARE ACCEPTED AT CENTRAL BIDDING. CENTRAL BIDDING CAN BE ACCESSED AT [www.centralbidding.com](http://www.centralbidding.com).

THE TANGIPAHOA PARISH GOVERNMENT RESERVES THE RIGHT TO REJECT BIDS IN ACCORDANCE WITH THE LAW.

S/DONNA DOMIANO,  
PURCHASING AGENT

DAILY STAR  
PLEASE PUBLISH NOVEMBER 5, 12, & 19, 2019

---

**COUNCIL**

TRENT FORREST  
DISTRICT 1  
EMILE "JOEY" MAYEAUX  
DISTRICT 6

JAMES BAILEY  
DISTRICT 2  
LIONELL WELLS  
DISTRICT 7

LOUIS "NICK" JOSEPH  
DISTRICT 3  
DAVID P. VIAL  
DISTRICT 8

CARLO S. BRUNO  
DISTRICT 4  
HARRY LAVINE  
DISTRICT 9

H. G. "BUDDY" RIDGEL  
DISTRICT 5  
BOBBY CORTEZ  
DISTRICT 10

# S P E C I F I C A T I O N   P R O P O S A L

Data Code	Description	Weight Front	Weight Rear	Retail Price
<b>Price Level</b>				
	WESTERN STAR 4700 PRL-20T (EFF:04/30/19)			STD
<b>Data Version</b>				
	SPECPRO21 DATA RELEASE VER 019			N/C
<b>Vehicle Configuration</b>				
	4700 SET-FORWARD FRONT AXLE CHASSIS			
	2020 MODEL YEAR SPECIFIED			STD
	SET FORWARD AXLE - TRUCK			STD
	TRAILER TOWING PROVISION AT END OF FRAME	10	10	
	LH PRIMARY STEERING LOCATION			STD
<b>General Service</b>				
	TRUCK/TRAILER CONFIGURATION			N/C
	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)			STD
	CONSTRUCTION SERVICE			STD
	GOVERNMENT BUSINESS SEGMENT			N/C
	DIRT/SAND/ROCK COMMODITY			N/C
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS			STD
	MAXIMUM 8% EXPECTED GRADE			STD
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			STD
	WESTERN STAR VOCATIONAL WARRANTY			STD
	EXPECTED FRONT AXLE(S) LOAD : 18000.0 lbs			
	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs			

Application Version 11.1.602  
 Data Version PRL-20T.019  
 JP5831



10/02/2019 4:24 PM

Page 1 of 16

Data Code	Description	Weight Front	Weight Rear	Retail Price
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 64000.0 lbs			
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs			
<b>Truck Service</b>				
	END DUMP BODY			STD
	EXPECTED TRUCK BODY LENGTH : 0.0 ft			
<b>Engine</b>				
	CUM L9 350 HP @ 2000 RPM, 2200 GOV RPM, 1150 LB/FT @ 1400 RPM	-850	-70	
<b>Electronic Parameters</b>				
	75 MPH ROAD SPEED LIMIT			N/C
	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT			N/C
	PTO MODE ENGINE RPM LIMIT - 1100 RPM			N/C
	PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED			N/C
	PTO RPM WITH CRUISE SET SWITCH - 700 RPM			N/C
	PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM			N/C
	PTO MODE CANCEL VEHICLE SPEED - 5 MPH			N/C
	PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND			N/C
	PTO MINIMUM RPM - 700			N/C
	REGEN INHIBIT SPEED THRESHOLD - 5 MPH			N/C
<b>Engine Equipment</b>				
	2016-2019 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION			STD
	VEHICLE IS SUBJECT TO EPA GHG14/GHG17, DOES NOT HAVE REGULATORY VEHICLE SPEED LIMITER (VSL) OR AUTOMATIC ENGINE SHUTDOWN(AES)			N/C
	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)			
	STANDARD OIL PAN			STD
	ENGINE MOUNTED OIL CHECK AND FILL			STD
	ONE PIECE VALVE COVER			STD
	SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED			STD



Data Code	Description	Weight Front	Weight Rear	Retail Price
	DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE			STD
	(3) ALLIANCE MODEL 1231XOE, GROUP 31, 12 VOLT MAINTENANCE FREE 3375 CCA THREADEDSTUD BATTERIES, FCCC ONLY			N/C
	BATTERY BOX FRAME MOUNTED	35		
	SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB			N/C
	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			STD
	NON-POLISHED BATTERY BOX COVER			N/C
	LOW VOLTAGE BATTERY DISCONNECT AT 12.3 VOLTS FOR ISOLATED CIRCUITS WITH LOCAL ALARM			STD
	CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE			N/C
	AIR COMPRESSOR DISCHARGE LINE			STD
	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			STD
	CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH	20		N/C
	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE			STD
	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH			STD
	11 FOOT 06 INCH (138 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT			STD
	RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP			STD
	13 GALLON DIESEL EXHAUST FLUID TANK	35	10	
	100 PERCENT DIESEL EXHAUST FLUID FILL			
	STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING			STD
	LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			STD
	STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILOPIPE SHIELD			STD
	HORTON 2-SPEED DRIVEMASTER ADVANTAGE POLAREXTREME FAN DRIVE			



Data Code	Description	Weight Front	Weight Rear	Retail Price
	AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED			STD
	CUMMINS SPIN ON FUEL FILTER			N/C
	COMBINATION FULL FLOW/BYPASS OIL FILTER			N/C
	1300 SQUARE INCH ALUMINUM RADIATOR	-20		N/C
	MOUNTING FOR FIREWALL MOUNTED SURGE TANK			STD
	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			STD
	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			STD
	CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES			STD
	RADIATOR DRAIN VALVE			N/C
	LOWER RADIATOR GUARD			STD
	PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK HEATER	4		N/C
	PHILLIPS-TEMRO 150 WATT/115 VOLT OIL PREHEATER	4		N/C
	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			STD
	ALUMINUM FLYWHEEL HOUSING			STD
	ELECTRIC GRID AIR INTAKE WARMER			N/C
	DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH	-35		N/C

#### Transmission

	ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION	-110	-35	
--	--	------	-----	--

#### Transmission Equipment

	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV			N/C
	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES			N/C
	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			N/C
	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			N/C

Data Code	Description	Weight Front	Weight Rear	Retail Price
	PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			N/C
	SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			N/C
	PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			N/C
	SECONDARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE			N/C
	FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED			N/C
	NO REAR PTO TRANSMISSION RANGE			STD
	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN			N/C
	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED			N/C
	TRANSMISSION PROGNOSTICS - ENABLED 2013			N/C
	WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK			STD
	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK			N/C
	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)			N/C

#### Front Axle and Equipment

	DETROIT DA-F-18.0-5 18,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE			
	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			STD
	NON-ASBESTOS FRONT BRAKE LINING			STD
	CONMET CAST IRON FRONT BRAKE DRUMS			STD
	SKF SCOTSEAL PLUS XL FRONT OIL SEALS			N/C
	VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL			STD
	STANDARD SPINDLE NUTS FOR ALL AXLES			STD
	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS			STD
	STANDARD KING PIN BUSHINGS			STD
	TRW TAS-85 POWER STEERING			STD
	POWER STEERING PUMP			STD



Data Code	Description	Weight Front	Weight Rear	Retail Price
	2 QUART SEE THROUGH POWER STEERING RESERVOIR			STD
	STANDARD CUPS AND CONES (WHEEL BEARINGS) FRONT AND REAR			N/C
	SYNTHETIC 50W FRONT AXLE LUBE			STD
<b>Front Suspension</b>				
	18,000# TAPERLEAF FRONT SUSPENSION	-90		
	GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION			
	FRONT SHOCK ABSORBERS			N/C
<b>Rear Axle and Equipment</b>				
	RT-46-160 46,000# R-SERIES TANDEM REAR AXLE		420	
	5.38 REAR AXLE RATIO			N/C
	IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING			STD
	MXL 17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	-30	-30	
	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES			STD
	(1) INTERAXLE LOCK VALVE FOR TANDEM OR TRIDEM DRIVE AXLES			STD
	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH			STD
	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			STD
	NON-ASBESTOS REAR BRAKE LINING			STD
	ASPHALT SPREADER CLEARANCE REAR BRAKE GEOMETRY			N/C
	CONMET CASTLITE CAST IRON REAR BRAKE DRUMS		-50	
	SKF SCOTSEAL PLUS XL REAR OIL SEALS			N/C
	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS			STD
	HALDEX AUTOMATIC REAR SLACK ADJUSTERS			
	SYNTHETIC 75W-90 REAR AXLE LUBE			N/C
<b>Rear Suspension</b>				
	HENDRICKSON HAULMAAX @46,000#REAR SUSPENSION		280	
	HENDRICKSON HAULMAAX/ULTIMAAX - 10.50" RIDE HEIGHT			N/C



Data Code	Description	Weight Front	Weight Rear	Retail Price
	54 INCH AXLE SPACING			N/C
	HENDRICKSON HN, HAULMAAX AND ULTIMAAX SERIES STEEL BEAMS WITH BAR PIN			N/C
	FORE/AFT AND TRANSVERSE CONTROL RODS			N/C
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM)		60	
<b>Brake System</b>				
	WABCO 4S/4M ABS			STD
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			STD
	FIBER BRAID PARKING BRAKE HOSE			STD
	STANDARD BRAKE SYSTEM VALVES			STD
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			STD
*	WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER			N/C
*	AIR DRYER FRAME MOUNTED			N/C
	STEEL AIR BRAKE RESERVOIRS			STD
	PULL CABLE ON WET TANK, PETCOCK DRAIN VALVES ON ALL OTHER AIR TANKS			STD
<b>Trailer Connections</b>				
	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS			N/C
	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			N/C
	NO TRAILER CABLE RECEPTACLE			
	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME			
	NO TRAILER RECEPTACLE BRACKET			STD
<b>Wheelbase &amp; Frame</b>				
	5050MM (199 INCH) WHEELBASE			N/C
	7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI	250	110	
	1600MM (63 INCH) REAR FRAME OVERHANG			STD
	FRAME OVERHANG RANGE: 61 INCH TO 70 INCH			N/C
	CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 117.58 in			
	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 114.58 in			





Data Code	Description	Weight Front	Weight Rear	Retail Price
	CALC'D FRAME LENGTH - OVERALL : 278.76			
	FRAME HEIGHT TOP FRONT UNLADEN : 43.13 in			
	FRAME HEIGHT TOP FRONT LADEN : 39.58 in			
	FRAME HEIGHT TOP REAR UNLADEN : 43.76 in			
	FRAME HEIGHT TOP REAR LADEN : 41.2 in			
	CALCULATED FRAME SPACE LH SIDE : 23.0 in			N/C
	CALCULATED FRAME SPACE RH SIDE : 169.07 in			N/C
	CALC'D SPACE AVAILABLE FOR DECKPLATE : 117.78 in			
	SQUARE END OF FRAME			STD
	STANDARD WEIGHT ENGINE CROSSMEMBER			STD
	STANDARD CROSSMEMBER BACK OF TRANSMISSION			STD
	STANDARD MIDSHIP #1 CROSSMEMBER(S)			STD
	STANDARD REARMOST CROSSMEMBER			STD
	HEAVY DUTY SUSPENSION CROSSMEMBER			STD
	STANDARD WEIGHT REAR SUSPENSION CROSSMEMBER			STD
<b>Chassis Equipment</b>				
	16 INCH PAINTED STEEL BUMPER			STD
	REMOVABLE FRONT TOW HOOKS STORED ON THE CHASSIS FRAME	25		
	BUMPER MOUNTING FOR SINGLE LICENSE PLATE			STD
	FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS			STD
	GRADE 8 THREADED HEX HEADED FRAME FASTENERS			STD
*	EXTERIOR HARNESSSES WRAPPED IN CONDUIT			N/C
<b>Fuel Tanks</b>				
	100 GALLON/378 LITER ALUMINUM FUEL TANK - LH	20		
	25 INCH DIAMETER FUEL TANK(S)			STD
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS			STD
	FUEL TANK(S) FORWARD			STD
	PLAIN STEP FINISH			STD
	FUEL TANK CAP(S)			STD
	DAVCO 245 FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR	20		N/C



Data Code	Description	Weight Front	Weight Rear	Retail Price
	EQUIFLO INBOARD FUEL SYSTEM			STD
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			STD
	FUEL COOLER			STD
<b>Tires</b>				
	MICHELIN XZY-3 385/65R22.5 18 PLY RADIAL FRONT TIRES	130		
*	MICHELIN XDE M/S 11R22.5 14 PLY RADIAL REAR TIRES		152	N/C
<b>Hubs</b>				
*	CONMET PRESET PLUS IRON FRONT HUBS			N/C
*	CONMET PRESET PLUS IRON REAR HUBS			N/C
<b>Wheels</b>				
	ACCURIDE 29807 22.5X12.25 10-HUB PILOT 4.75 INSET 5-HAND STEEL DISC FRONT WHEELS	98		
	MAXION WHEELS 90262 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS		72	
	NO FRONT HUB COVERS			STD
	FRONT WHEEL MOUNTING NUTS			STD
	REAR WHEEL MOUNTING NUTS			STD
<b>Cab Exterior</b>				
	110 INCH BBC STEEL CONVENTIONAL CAB			STD
	WESTERN STAR PAINTED ALUMINUM CAB SKIRT			STD
	AIR CAB MOUNTS WITH CHECK VALVE			STD
	NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE			STD
	NO SLEEPER DOOR	-15		STD
	FRONT FENDERS			STD
	2 INCH FENDER EXTENSIONS	5		
	LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERTS AND RH INTERIOR GRAB HANDLE MOUNTED TO A POST			STD
	STATIONARY BRIGHT FINISH GRILLE			STD
	CHROME HOOD MOUNTED AIR INTAKE GRILLE			STD
	GALVANEALD STEEL SEVERE SERVICE CAB			STD
	FIBERGLASS HOOD			STD
	DUAL ROUND AIR HORNS, SINGLE BASE, MOUNTED UNDER CAB			
	SINGLE ELECTRIC HORN			STD



Data Code	Description	Weight Front	Weight Rear	Retail Price
	DOORS AND IGNITION KEYED THE SAME (3 KEYS)			
	REAR LICENSE PLATE MOUNT END OF FRAME			STD
	SINGLE RECTANGULAR SEALED BEAM HEADLIGHTS WITH BRIGHT BEZELS			STD
	(5) AMBER MARKER LIGHTS			STD
	DAYTIME RUNNING LIGHTS			
	INTEGRAL STOP/TAIL/BACKUP LIGHTS			STD
	STANDARD FRONT TURN SIGNAL LAMPS			STD
	DUAL WEST COAST STAINLESS STEEL MIRRORS			STD
	DOOR MOUNTED MIRRORS			STD
	102 INCH EQUIPMENT WIDTH			STD
	LH AND RH 8 INCH STAINLESS STEEL CONVEX MIRRORS MOUNTED BELOW PRIMARY MIRRORS			STD
	RH DOWN VIEW MIRROR			STD
	STANDARD SIDE/REAR REFLECTORS			STD
	STAINLESS STEEL EXTERIOR SUN VISOR	28		
	17.5X35 INCH TINTED REAR WINDOW			STD
	TINTED DOOR GLASS			STD
	MANUAL DOOR WINDOW REGULATORS			STD
	2-PIECE TINTED CURVED GASKET MOUNTED WINDSHIELD			STD
	2 GALLON WINDSHIELD WASHER RESERVOIR WITH FLUID LEVEL INDICATOR, MOUNTED UNDER CAB, WITH REMOTE FILL			STD

### Cab Interior

	GRAY VINYL BASE INTERIOR			STD
	BLACK HARD TRIM			STD
	BASE LEFT HAND DOOR TRIM			STD
	BASE RIGHT HAND DOOR TRIM			STD
	BLACK MATS WITH SINGLE INSULATION			STD
	DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE			STD
	NO STORAGE-CAB INT,LH WALL,LOWER	-20	-10	STD
	NO STORAGE-CAB INT, RH WALL, LOWER	-20	-10	STD
	NO STORAGE-CAB INT,LH WALL,UPPER	-20	-10	N/C
	NO STORAGE-CAB INT,RH WALL,UPPER	-20	-10	STD
	FORWARD ROOF MOUNTED CONSOLE			STD
	LH AND RH DOOR MAP POCKETS			STD

Data Code	Description	Weight Front	Weight Rear	Retail Price
	(2) COAT HOOKS ON BACKWALL OF CAB NO CUP/THERMOS HOLDER			STD
	TWO-TONE CHARCOAL UPPER/COOL GRAY LOWER SOFT TOUCH WING DASH WITH BLACK DRIVER SIDE COSMETIC UNDER DASH COVER			STD
	STANDARD WIRING			N/C
	5 LB. FIRE EXTINGUISHER	10		
	HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL			
	HVAC DUCTING WITH FOAM MAIN FRESH AIR FILTER			N/C
	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH			STD
	NO AUXILIARY HVAC UNIT	-10	-10	STD
	STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES			
	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR			STD
	RADIATOR MOUNTED AIR CONDITIONER CONDENSER			STD
	BINARY CONTROL, R-134A			STD
	CAB INSULATION			STD
	AUTOMATIC SELF-RESET CIRCUIT BREAKER IN MAIN DASH POWER DISTRIBUTION BOX AND CIRCUIT BREAKER/FUSE IN AUXILIARY POWER DISTRIBUTION BOXES			N/C
	DOOR ACTIVATED DOME LIGHT, UNDER DASH LIGHT AND LH AND RH DOOR MOUNTED COURTESY LIGHTS			STD
	CAB DOOR LATCHES WITH MANUAL DOOR LOCKS			STD
	NO MATTRESS	-15		STD
	(2) 12 VOLT POWER RECEPTACLES MOUNTED IN DASH			N/C
	TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10		
	BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND REAR CUSHION TILT			STD
	BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT			
	DUAL DRIVER AND PASSENGER SEAT ARMRESTS	8		

Data Code	Description	Weight Front	Weight Rear	Retail Price
	GRAY VINYL DRIVER SEAT COVER			
	GRAY VINYL PASSENGER SEAT COVER			
	3 POINT HIGH VISIBILITY ORANGE RETRACTOR DRIVER AND PASSENGER SEAT BELTS			
	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN			STD
	4-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL WITH SWITCHES			
	DRIVER AND PASSENGER INTERIOR SUN VISORS			STD
<b>Instruments &amp; Controls</b>				
	NON-ADJUSTABLE SUSPENDED PEDALS			STD
	ELECTRONIC FOOT ACCELERATOR			STD
	BRIGHT ARGENT FINISH GAUGE BEZELS			STD
	BLACK DRIVER INSTRUMENT PANEL			N/C
	BLACK CENTER INSTRUMENT PANEL			N/C
	LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM			STD
	2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES			STD
	INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS			STD
	87 DB TO 112 DB SELF-ADJUSTING BACKUP ALARM		3	
	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES			STD
	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			STD
	ICU4ME DRIVER MESSAGE CENTER WITH GRAPHICAL DISPLAY, BLACK FACE GAUGES, DIAGNOSTICS AND DATA LINKED			STD
	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH			STD
	2 INCH ELECTRIC FUEL GAUGE			STD
	PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE			N/C
	NO ADDITIONAL EXTRA SWITCH ACCUATORS			STD
N	NO CUSTOMER INTERFACE CONNECTOR			STD
	NO PREWIRED HIGH POWER CIRCUIT			STD
	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			STD



Data Code	Description	Weight Front	Weight Rear	Retail Price
	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			STD
	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER			STD
	ELECTRIC ENGINE OIL PRESSURE GAUGE			STD
	AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH AND USB AND AUXILIARY INPUTS, J1939	10		
	ROOF/OVERHEAD CONSOLE MOUNTED RADIO			N/C
	(4) RADIO SPEAKERS IN CAB			N/C
	AM/FM ANTENNA MOUNTED ON LH FRONT A-PILLAR	2		
	POWER AND GROUND WIRING FOR CB RADIO IN OVERHEAD CONSOLE			STD
	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION			
	MULTI-BAND AM/FM/WB/CB LH MIRROR MOUNTED ANTENNA SYSTEM			STD
	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITH ODOMETER			STD
	STANDARD VEHICLE SPEED SENSOR			STD
	ELECTRONIC 3000 RPM TACHOMETER			STD
	NO VEHICLE PERFORMANCE MONITOR	-5		
	IGNITION SWITCH CONTROLLED ENGINE STOP			STD
	TWO EXTRA SWITCHES IN DASH			
	HARDWIRE SWITCH #1,ON/OFF LATCHING, 20 AMPS IGNITION WIRED TO BACK OF CAB			
	HARDWIRE SWITCH #2,ON/OFF LATCHING, 20 AMPS IGNITION WIRED TO BACK OF CAB			N/C
	NO HARDWIRE SWITCH #3			STD
	NO HARDWIRE SWITCH #4			STD
	NO HARDWIRE SWITCH #5,ON/OFF LATCHING, WIRED TO CUSTOMER INTERFACE CONNECTOR			STD
	NO HARDWIRE SWITCH #6,ON/OFF LATCHING, WIRED TO CUSTOMER INTERFACE CONNECTOR			STD
	NO HARDWIRE SWITCH #7,ON/OFF LATCHING, WIRED TO CUSTOMER INTERFACE CONNECTOR			STD
	NO HARDWIRE SWITCH #8,ON/OFF LATCHING, WIRED TO CUSTOMER INTERFACE CONNECTOR			STD



Data Code	Description	Weight Front	Weight Rear	Retail Price
	NO HARDWIRE SWITCH #9,ON/OFF LATCHING, WIRED TO CUSTOMER INTERFACE CONNECTOR			STD
	NO HARDWIRE SWITCH #10,ON/OFF LATCHING,WIRED TO CUSTOMER INTERFACE CONNECTOR			STD
	BW TRACTOR PROTECTION VALVE			N/C
	TRAILER HAND CONTROL BRAKE VALVE			N/C
	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			STD
	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY			STD
	CAB/TRAILER MARKER LIGHT SWITCH WITH SEPARATE HEADLIGHT SWITCH WITH HEADLIGHT/MARKER LIGHT INTERRUPTER SWITCHES ON STEERING WHEEL			STD
	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR			N/C
	SELF CANCELING TURN SIGNAL SWITCH, HEADLAMP HIGH/LOW AND FLASH, WASH/WIPE/INTERMITTENT			
	PACIFIC INSIGHT ELECTRONIC FLASHER			STD
<b>Design</b>				
	PAINT: ONE SOLID COLOR			STD
<b>Color</b>				
	CAB COLOR A: L0006EB WHITE ELITE BC			STD
	CAB INTERIOR PAINTED SAME AS CAB COLOR			STD
	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT			STD
	POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)			STD
	POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW)			STD
	BUMPER PAINTED SAME AS CHASSIS			STD
<b>Certification / Compliance</b>				
	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS			STD
<b>Raw Performance Data</b>				
	CALC'D FRAME LENGTH - OVERALL : 278.76			
	CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 114.58 in			



Data Code	Description	Weight Front	Weight Rear	Retail Price
	CALC'D SPACE AVAILABLE FOR DECKPLATE : 117.78 in			

**Sales Programs**

NO SALES PROGRAMS HAVE BEEN SELECTED

**TOTAL VEHICLE SUMMARY**

**Adjusted List Price**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight*	8564 lbs	7502 lbs	16066 lbs
Total Weight*	8564 lbs	7502 lbs	16066 lbs

**ITEMS NOT INCLUDED IN ADJUSTED LIST PRICE**

**Other Factory Charges**

STANDARD DESTINATION CHARGE

(+) Weights shown are estimates only.

If weight is critical, contact Customer Application Engineering.

(\*\*) Prices shown do not include taxes, fees, etc... "Net Equipment Selling Price" is located on the Quotation Details Proposal Report.





(\*\*\*) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Application Version 11.1.602  
Data Version PRL-20T.019  
JP5831



10/02/2019 4:24 PM

Page 16 of 16

		QTY	Unit Price	Ext. Price
4	F-14			
	DUMP BODY - FRAME TYPE - 14'	EA		
	Yardage: 13/15			
	Floor Material: 3/16 A1011			
	Front / Material: 56" 10 GA A1011			
	Side / Material: 42" 10 GA A1011			
	Vertical Side Brace: Yes			
	Horizontal Brace: No			
	Hoist / Cylinder: VTW-63110			
	Hydraulics: Yes			
4	TAILGATE	Each	\$0.00	\$0.00
	Air Operated: Yes			
	Panel: 9			
	Material: 7 GA A1011			
	Height: 50"			
	Slope: None			
	Chains: 5/16"			
	Double Acting: Yes			
	High Lift Gate: No			
	Side Swing - Ground Operated: No			
	Center Opening: No			
	Material Gate: None			
	Water Tight: None			
4	DB OPTIONS # 1	Each	\$0.00	\$0.00
	Cabshield: Full Width-1/2 (24")			
	Asphalt Apron: 8" push type			
	Bolt On: No			
	Center Board Pockets Yes			
	Lights: LED Standard			
	Oval S/T/T: None			
	Clear Backup: No			
4	DB OPTIONS # 2	Each	\$0.00	\$0.00
	D/S & P/S step			
	1/4 x 2 tarp tie rail			
	7 ga cab shield			
	Plumb c/f air & elec to rear			
4	INSTALL	Each	\$0.00	\$0.00
	Hydraulic Hoses/Fittings: Yes			
	Pump: 35 gal w/air shift CW (400-80261)			
	Console: Clutch Shift Air			
	Conspicuity Tape: No			
	Mudflaps and Brackets: Yes			
	Chrome Turnouts: No			
	Splash/Gravel Guards: No			
	Side Boards: Hardwood - 2x8			
	Covers: No			
	Wires in Conduit No			
	Delivery Fuel/Charges: No			

			UOM	Unit Price	Ext. Price
8.00	PAINT	ANY STANDARD WARREN PAINT	GAL	\$0.00	\$0.00
4	PTO	Color: Warren Black (800-80007) FOR ALLISON 3000 SERIES TRANSMISSION	EA	\$0.00	\$0.00
4	TARP SYSTEM	TARP system - installed Installation: Installed Brand: Donovan Manual / Electric: Electric Type: Arm Aluminum / Steel: Aluminum Bent Arm: No Tarp Size: 90"x18' Tarp Type: Mesh Side Flaps: No	EA	\$0.00	\$0.00
4	TOW PACKAGE	Pintle Plate: 3/4" Pintle Hitch: 30 Ton Glad Hands: Yes D Rings: Yes Tow Hooks: No Electric Plug: 7 Way Pup Rigging: No	Each	\$0.00	\$0.00

QUOTATION VALID FOR 30 DAYS

Subtotal	
Misc	\$0.00
Tax	\$0.00
Ship & Handling	\$0.00
Trade In Allowance	\$0.00
Total	

BID SHEET

TWO (2) OR MORE NEW OR CURRENT MODEL

12-16 YARD HEAVY DUTY WARREN OR EQUIVALENT DUMP BODY (MINIMUM 62,500 LBS)

WESTERN STAR 4700 SB OR APPROVED EQUAL

DECEMBER 5, 2019

BIDDER NAME

---

ADDRESS

---

PHONE

---

REPRESENTATIVE

---

YEAR/MAKE/MODEL

---

TOTAL BID FOR EACH

---

DELIVERY DATE

---

WARRANTY INFORMATION INCLOSED \_\_\_ YES \_\_\_ NO

---

SIGNATURE

---

DATE